
Technical Sheet

AB55365
AB55365

Suitable for joining wood to wood or wood-concrete joints, for uniform load is recommended to use two brackets on each link material







Features

Material

Steel quality:

S250GD + Z275 according to DIN EN10346

Corrosion protection:

275 g / m galvanized on both sides 20mm

Benefits

• Connection through a variety of screws, nails and mechanical anchors.
applicable materials
• suitable for connections wood-wood, concrete, steel

Applications

Applicatons

• For timber-to-timber connections with smaller dimensions, installation of windows, sills

Scope


- For timber-to-timber connections with smaller dimensions, e.g. purlins on the main beams, installation of windows


Technical Sheet

AB55365
AB55365

SIMPSON Strong-Tie

Technical Data






Product Dimensions

Reference	Connector Dimensions											
	Other				Product Dimensions[mm]				Joist		Flange B	
									Round		Round	
	Tun / DB nr.	NOB nr.	Qty per Box	Weight[kg]	A[mm]	B[mm]	C[mm]	Thickness[mm]	∅[mm]	Ø8.5[mm]	Ø5[mm]	Ø8.5[mm]
AB55365	1386018	42948106	100.0	0.13	65	65	55	2.5	8	1	8	1

Installation

Fasteners

- **Connecting with screws or nails CSA5,0xl CNA4,0xl**
- **For installation in concrete use anchor bolts M8**



Copyright by Simpson Strong-Tie®