Technical Sheet


AB55365S

AB55365S - stainless steel bracket

Suitable for joining wood to wood or wood-concrete joints, for uniform load is recommended to use two brackets on each link







Features

Material

- **Stainless steel 1.4401 or 1.4404 (V4A), in accordance with EN10088.**
- **Resistance to acid - A4**

Benefits

- **Connection through a variety of screws, nails and mechanical anchors.**

Applications

Applicatons

Suitable for connections wood-wood, concrete, steel

Scope

- **For timber-to-timber connections with smaller dimensions, installation of windows, sills installation.**


Technical Sheet


AB55365S

AB55365S - stainless steel bracket

Technical Data

Product Dimensions






Reference	Connector Dimensions											
	Other				Product Dimensions[mm]				Joist		Flange B	
	Tun / DB nr.	NOB nr.	Qty per Box	Weight[kg]	A[mm]	B[mm]	C[mm]	Thickness[mm]	Round		Round	
									∅[mm]	Ø8.5[mm]	Ø5[mm]	Ø8.5[mm]
AB55365S-B	1454180	43893844	100.0	0.13	65	65	55	2.5	8	1	8	1

Installation

Fasteners

- **connections using screws or nails CSA5,0xl CNA4,0xl**
- **For installation in concrete use anchor bolts M8**



Copyright by Simpson Strong-Tie®