
Technical Sheet

DSZ
Adjustable Door Frame Screw

This special frame screw is used for indoor installation of interior door frames with pre-drilled holes - Ø14 mm from one side and Ø6 mm from the other. The anchor thread under the head grips the woodwork, allowing the frame to be adjusted both inwards and outwards.






Features

Benefits

- Countersunk head
- Fastening wire under the head: adjust the frame inwards and outwards at the same time
- Type 17 anti-friction point

DSZ
Adjustable Door Frame Screw

Technical Data



Product dimensions

Reference	Fasteners Dimensions								
	Item Code	Other	Product Dimensions[mm]						
		Weight[kg]	d[mm]	l[mm]	d_h[mm]	d1[mm]	lg[mm]	lp[mm]	bit[mm]
DSZ6.0X60	75552	0.011	6	60	11.7	4	30	20	T-25
DSZ6.0X70	75553	0.012	6	70	11.7	4	40	20	T-25
DSZ6.0X80	75554 - 75711	0.012	6	80	11.7	4	50	20	T-25
DSZ6.0X90	75712 - 75555	0.018	6	90	11.7	4	60	20	T-25
DSZ6.0X100	75556	0.02	6	100	11.7	4	60	20	T-25
DSZ6.0X110	75557	0.022	6	110	11.7	4	60	20	T-25
DSZ6.0X120	75558	0.022	6	120	11.7	4	60	20	T-25
DSZ6.0X130	75559	0.024	6	130	11.7	4	60	20	T-25

Copyright by Simpson Strong-Tie®