
Technical Sheet

ACR4712
Angle bracket

ACR4712 angle brackets are used for smaller timber dimensions in wood-wood assemblies or for assembly between wooden beam and concrete.
Each assembly requires two angle brackets.





Features

Materials

- Steel quality: Pre-galvanised S250GD & Z275 according to EN10346
- Corrosion protection: 275 g/m2 on both sides with a zinc thickness on 20 µm
- The angle bracket is also available in stainless steel: ACR4712S

Benefits

- Light and small multifunctional connectors
- New and improved version of AC35350 angle bracket
- With double rib reinforcement

Applications

Suitable On

- Wood-wood assemblies
- Wood-concrete assemblies


Other


Used in assemblies with smaller timber dimensions

Technical Sheet

ACR4712
Angle bracket

Technical Data






Product Dimensions

Reference	Connector Dimensions											
	Other				Product Dimensions[mm]				Joist		Flange B	
									Round		Round	
	Tun / DB nr.	NOB nr.	Qty per Box	Weight[kg]	A[mm]	B[mm]	C[mm]	Thickness[mm]	Ø[mm]	Ø8[mm]	Ø5[mm]	Ø8[mm]
ACR4712	1544663	45155952	100.0	0.029	48	48	37	1.25	5	1	5	1

Installation

Fixing

- In wood: CNA4,0xℓ nails or CSA5,0xℓ screws
- In concrete: M8 bolt



Copyright by Simpson Strong-Tie®