Technical Sheet

BNSP

BNSP - winbracing system

BNSP clamping device must be permanently mounted and tightened.



Features

Material

Steel quality:
S 250 GD + Z 275 according to DIN EN 10346
Corrosion protection:
275 g / m galvanized on both sides 20mm
- **Screws: Quality 8.8**
- **Trn:**

Steel quality:
S 235 JR according to EN 10025 DIN
Corrosion protection:
Galvanizing layer thickness of about 55 microns in accordance with DIN EN 1461

Benefits

- **Connection tapes with other clamping elements and the subsequent withdrawal.**
- **When using any screws or pins are the ultimate common connector always more than just connecting tape**

Applications

Applicable materials

- **Fasteners BNK, BNF, BNG**

Application area


- **From an economic application of Simpson Strong-Tie bracing belt, there are other products that have been developed for simple solutions to connectivity problems. In summary, the products of this group are called bracing systems**
- **They are available for the respective widths 25, 40 and 60 mm**
- **To connect the 80 mm tapes up to 60 items of the system can be used.**
- **bracing system can be easily clamped by means BNSP or products BNF or BNK BNG (see following pages)**
- **When turning threaded rods right / left hand, there is another option tension.**
- **The connection between the connection lugs of the belt is achieved CLIPS20 or CLIPS23 on other products cotter**


Technical Sheet

BNSP
BNSP - winbracing system

Technical Data

Dimensions







Reference	Connector Dimensions												Bracing capacity	
	Other						Product Dimensions[mm]			Holes			Strap fasteners attached to	
	Tun / DB nr.	NOB nr.	For use with strap width	Kit composition	Qty per Box	Weight[kg]	A[mm]	B[mm]	C[mm]	Diameter	Left (number)	Right (number)	Tape	BNF: BNG: BNK
BNSP80-B	8271264	21217146	BANxx80xx	2 x BF4060M5; 4 x BF25M5	4	1.8	300-360	80	35	5 + 21	11 + 0	8 + 1	x	x


Installation


Installation


- **CLIPS20 bzw.CLIPS23**











Copyright by Simpson Strong-Tie®