Technical Sheet

BNKK
Coupler

For a secure connection tape.





Features

Material

Steel quality:
S250GD + Z275 according to DIN EN10346
Corrosion protection:
275 g / m galvanized on both sides 20mm
- **Screws: Quality 8.8**
- **Trn:**

Steel quality:
S 235 JR according to DIN EN 10025

Benefits

- **Connection tapes without further extension is possible with the coupling connector BNKK.**
- **When using any screws or pins are common load connector always greater than the tape itself or the connection connector.**

Applications

Applicable materials


- **To connect the X-shaped strip**


Technical Sheet

BNKK
Coupler

Technical Data

Dimension






Reference	Connector Dimensions												
	Other								Product Dimensions[mm]			Holes	
	Tun / DB nr.	NOB nr.	Suitable with	Included clips/screws	Included bolts	Socket pins supplied	Box Quantity	Weight[kg]	A[mm]	A[mm]	t[mm]	Ø	Qty
BNKK25-14	1561275	45951693	BANXX25XX	1 x BF25M5	Dorn Ø14 m/sikringssplit	-	4	0.25	125	36	2+2+2=6	5 + 15	3 + 1
BNKK40/60-14	1561276	45951916	BANXX40, BANXX60XX	2 x BF4060M5	Dorn Ø14 m/sikringssplit	-	4	0.38	157	60	2+3+2=7	5 + 15	7 + 1
BNKK25-B	-	-	BANXX25XX	3 x M5	Dorn Ø12 m/sikringssplit	-	4	0.17	125	36	2+2+2=6	5 + 12.5	3 + 1
BNKK40/60-B	-	-	BANXX40, BANXX60XX, BANXX80XX	2 x BF4060M5*	Dorn Ø20 m/sikringssplit	1 Ø20**	4	0.36	157	60	2+3+2=7	5 + 21	7 + 1


* For connection with BAN1580.... an additional CLIPS20 (or 2 x M5 in 8.8) must be installed and ordered


Installation


Application area

- **To connect the X-shaped strip**









Copyright by Simpson Strong-Tie®