Technical Sheet

DSPIX4

Decking Screw Pro - Impreg®X4

The decking screw is designed for treated timber. It has a 6 lobe recess to ensure good grip. The cut point drives the screw efficiently and prevents splitting.
The upper thread helps pull the timber tight up against the substrate. Although the screw is wider than the DISX, the narrow cap head provides a more dicrete, yet robust installation.





Features

Features

- 6 Lobe drive.
- Cap head.
- Coarse thread.
- Type 17 point.
- Impreg® X4 coating.


Applications

Suitable For

- Decking to timber.

DSPIX4
Decking Screw Pro - Impreg®X4

Technical Data



Product Dimensions

Reference	Fasteners Dimensions										
	Item Code	Other			Product Dimensions[mm]						
		Tun / DB nr.	NOB nr.	Weight[kg]	d[mm]	l[mm]	d_h[mm]	d_1[mm]	lg_1 [mm]	lg_2 [mm]	Driver Bit[mm]
DSPIX44.8X60	74356	1949815	53293705	0.005	4.8	60	6.5	3.1	26	12	T-20
DSPIX44.8X70	74357	1949816	53293713	0.005	4.8	70	6.5	3.1	32	18	T-20
DSPIX45.5X80	74358	1949817	53293724	0.009	5.5	80	7	3.8	37.5	20	T-25
DSPIX46.5X95	74359	1949818	53293732	0.015	6.5	95	8	4	40	29	T-30

Product characteristic properties

Reference	Screw Parameters				
	Characteristic parameters				
	Characteristic Yield Moment – $My,_k$[Nm]	Characteristic withdrawal parameter - $f_{ax,k,90°}$[N/mm²]	Characteristic head pull-through parameter - $f_{head,k}$[N/mm²]	Characteristic tensile capacity - $f_{tens,k}$[kN]	Torsional ratio
DSPIX44.8X60	5951	15.1	32.2	7.9	1.8
DSPIX44.8X70	5951	15.1	32.2	7.9	1.8
DSPIX45.5X80	11193	15.7	33.3	12.2	1.8
DSPIX46.5X95	13203	15.8	45.7	12.9	1.5

Copyright by Simpson Strong-Tie®