
Technical Sheet

GK
Drywall to Wood or Steel Screw

Drywall screw is used indoors for fixing to timber battens and steel joists with a maximum thickness of 1.0 mm.
The duplex head prevents the paper on the plasterboard tearing on fitting.





Features

Features

- Cross point head.
- Bugle Head.
- Sharp point
- High-low thread.
- Electrogalvanised coating.

Applications

Suitable For

- Drywall to timber.
- Drywall to steel.

Technical Data

Product Dimensions

Reference	Fasteners Dimensions									
	Item Code	Other			Product Dimensions[mm]					
		Tun / DB nr.	NOB nr.	Weight[kg]	d[mm]	l[mm]	dh[mm]	d1[mm]	lg[mm]	bit[mm]
GK3.9X30	74299	1949829	53296085	0.002	3.9	30	8	3.2	25.5	PH2
GK3.9X40	74301	1949831	53296104	0.002	3.9	40	8	3.2	35.5	PH2
GK3.9X55	74303	1949833	53292574	0.003	3.9	55	8	3.2	50.5	PH2

GK Collated Screws

Reference	Fasteners Dimensions								
	Item Code	Other		Product Dimensions[mm]					
		Tun / DB nr.	NOB nr.	d[mm]	l[mm]	dh[mm]	d1[mm]	lg[mm]	bit[mm]
GK3.9X30 Collated	74296	1949826	53292377	3.9	30	8	3.2	25.5	PH2
GK3.9X40 Collated	74297	1949827	53292381	3.9	40	8	3.2	35.5	PH2
GK3.9X55 Collated	74298	1949828	53292396	3.9	55	8	3.2	50.5	PH2

* Flat tape collated for standard auto-feed screwdrivers

Copyright by Simpson Strong-Tie®