
Technical Sheet

GAF
Fork anchor

Fork Anchor GAF is used for anchoring rafters with a width of 45-50 mm to the underlying wooden structure. GAF can also be used for fastening top battens or top plates in tiled roofs.







Features

Material

s

Applications

Application

- Used for anchoring rafters
- Used for fastening top battens or top plates in tiled roofs

Suitable On


- **Supporting member:** solid wood, composite lumber.
- **Supported member:** composite lumber.

Technical Sheet

GAF
Fork anchor

Technical Data

Dimension





Reference	Connector Dimensions										
	Other			Product Dimensions[mm]						Holes[mm]	
	DB. nr.	NOB nr.	Weight[kg]	A[mm]	B[mm]	C[mm]	D[mm]	E[mm]	t[mm]	Diameter[mm]	Qty
GAF48	8978272	21593868	0.2	50	138	178	26	60	1.5	4	9 + 9 + 16

Load carrying capacity table (characteristic values)


Reference	Ties capacity			
	Number of Fasteners			Characteristic capacity
	Type[mm]	Qty in lower part	Qty	
GAF48	CNA3,1x40	5	3 + 3	7.1

The load-bearing capacities are only valid for roof pitches below 60°.

Installation

Fixing

s



Copyright by Simpson Strong-Tie®