
Technical Sheet

CSFT
Full Thread Connector Screw

CSFT connector screw is designed for steel to wood connections and load rated togehter with specific Simpson Strong-Tie connectors. The new head shape ensure a good fit in the connector and the full thread increase the load bearing capacity. The flat head makes it possible to get a flush surface after installation.





Features

Features

- CE Marked (EN14592)
- Fully threaded
- Zinc flake coating
- 6 lobe drive
- Special head shape designed for SST connectors

Applications

Suitable for

- Wood to wood

CSFT
Full Thread Connector Screw

Technical Data

Product Dimensions

Reference	Fasteners Dimensions								
	Item Code	Product Dimensions[mm]						Other	
		d[mm]	l[mm]	d_h[mm]	d_1[mm]	lg[mm]	bit[mm]	Qty/box	Weight[kg]
CSFT5.0X70	77308	5	70	8.5	3.5	65	T-20	100.0	0.006
CSFT6.0X85	77309	6	85	9.5	4	79	T-25	100.0	0.01
CSFT6.0X110	77310	6	110	9.5	4	103	T-25	100.0	0.013

Characteristic properties

Reference	Screw Parameters			
	Characteristic parameters			
	Characteristic Yield Moment My,k[Nm]	Characteristic Withdrawal Parameter fax,k,90° [N/mm²]	Characteristic Tensile Capacity ftens,k[kN]	Torsional ratio
CSFT5.0X70	7.7	17.8	10.7	>1,5
CSFT6.0X85	10.5	13.6	12.9	>1,5
CSFT6.0X110	10.5	13.6	12.9	>1,5

Copyright by Simpson Strong-Tie®