**Technical Sheet**

BANS / BANW
**Punched straps**

Punched straps for constructive purposes, such as cable fasteners or pipe hangers. Practilettband is available in 4 dimensions on reel with a length of 10 m.



## Features

### Material

- Produced of galvanized steel

## Applications

### When to Use

- For pipe fittings and other types of suspension
- For connections in wood for hobby purposes

**Practilettbands must not be used for stiffening and anchoring in building structures (for this purpose wind straps must are used).**




BANS



BANW





BANS-H5



BANS / BANW
**Punched straps**

# Technical Data






## Dimensions and drill holes

| Reference | Connector Dimensions | | | | | | |
|---|---|---|---|---|---|---|---|
| | Other | | | Product Dimensions[mm] | | | Holes[mm] |
| | Tun / DB nr. | NOB nr. | Weight[kg] | A[mm] | B[mm] | t[mm] | Ø[mm] |
| BANW071210 | 1761814 | 49004196 | 0.49 | 12 | 10 | 0.7 | 5 |
| BANW071710 | 1761819 | 49004480 | 0.7 | 17 | 10 | 0.7 | 7 |
| BANW071725 | 1761821 | 49004525 | 1.6 | 17 | 25 | 0.7 | 7 |

# Installation

## Fixing

- Fasteners must be adapted to the tape thickness, the hole sizes and the material to be connected by the band.



Copyright by Simpson Strong-Tie®