
Technical Sheet

ARA2

Ring Shank Wood to Wood Nail - Stainless Steel (A2)


This ring shank nail with its low oval head and ring shank is used to fix timber components to wood, where high pull-out strength is required. Stainless A2 can withstand all weather conditions. Is also used for laying roofing tiles.






ARA2
Ring Shank Wood to Wood Nail - Stainless Steel (A2)

Technical Data





Product Dimensions

Reference	Fasteners Dimensions										
	Item Code	Other			Product Dimensions[mm]						
		Tun / DB nr.	NOB nr.	Weight[kg]	d[mm]	l[mm]	dh[mm]	A_h[mm]	ht[mm]	lg[mm]	lp[mm]
ARA23.1X75	74218	1950547	53292797	0.005	3.1	75	7.5	44.2	1.6	50	4.3

Product characteristic properties

Reference	Nail characteristic parameters			
	Characteristic parameters			
	Characteristic Yield Moment My,k[Nm]	Characteristic Withdrawal Parameter fax,k,90°[N/mm²]	Characteristic Head Pull-Through Parameter fhead,k[N/mm²]	Characteristic tensile capacity - $f_{tens,k}$[kN]
ARA23.1X75	3926	7.4	-	5.2

Copyright by Simpson Strong-Tie®