Technical Sheet

RDPF
Screw for drywall

RDPF screws have been studied to accpet high speed insertion of screws leading to a quick installation of dense plasterboard type "Diamond Board®" taking care of the support.





Features

Material

- Gray phosphate finish.

Benefits

- Flat head countersunked to be flush with the plate,
- Tapered tip for good penetration even without pre-drilling,
- Reverse thread for easy removal of plaster dust,
- High-low thread for fixing in timber or steel,
- 4.2 mm diameter to prevent the screw from breaking when tightened,
- CE marking according to EN14566: characteristic load values on steel (pull-out & shear).

Applications

Header member

- Fiber reinforced drywall.


Applications

- Plasterboard on timber supports and metal rails.

Technical Sheet


RDPF
Screw for drywall

Technical Data



Dimensions and caracteristics values

Reference	Fasteners Dimensions							
	Product Dimensions[mm]				QD information			Other
	Ø Head[mm]	Thread diameter[mm]	l[mm]	Thread length[mm]	Screws qty per strip	Compatible device	Max. rotation speed[tr/min]	Screws qty per box
RDPF40PE	7.8	4.1	40	31.5	30.0	QDPR051E / QD76KE	4000	2500.0




Dimensions and technical data - DE

Reference	Fasteners Dimensions					
	Product Dimensions[mm]			QD information		Other
	Ø Head[mm]	Thread diameter[mm]	l[mm]	Screws qty per strip	Compatible device	Screws qty per box
RDPF40PE	7.8	4.1	40	30.0	QDPR051E / QD76KE	2500.0

RDPF
Screw for drywall

Options



Smooth countersunk head



High-Low thread



Tapered tip

Copyright by Simpson Strong-Tie®