Technical Sheet

DTHQ
Trim Head Decking Screw

The DTHQ is a trim head screw with coarse thread suitable for timber to timber applications such as decking. It has a Type 17 point which eliminates the need for pre-drilling and reduces the installation torque. The trim head provides a neat finish when countersunk into the timber and the Quik Guard® coating allows the screw to be used in external environments.







BIT2SUE

Features

Material

Steel - Quik Guard® coating

Benefits

- Type 17 point for faster, straighter drilling and reduced insertion torque
- Counter sunk trim head for a neater finish
- Coarse thread
- Quik Guard coating prevents rust staining and prolonges life, even outdoors
- Driver bits included (BIT2SUE)

Applications

Common Applications

- Decking
- Timber to timber


DTHQ
Trim Head Decking Screw

Technical Data



Dimensions

Reference	Fasteners Dimensions							
	Other				Product Dimensions[mm]		QD information	
	DB No.	NOBB No.	Screws qty per box	Weight[kg]	Width[mm]	l[mm]	Qty per Strip	Recommended RPM[tr/min]
DTHQ51E	5384679	25254863	2000.0	6.6	6.2	51	30.0	2500.0
DTHQ64E	5385128	25254871	1500.0	6.2	6.2	64	30.0	2500.0
DTHQ76E	5384689	29194024	1000.0	6.2	6.2	76	30.0	2500.0





Product Dimensions UK

Reference	Fasteners Dimensions								
	Product Dimensions[mm]				QD information			Other	
	d_h[mm]	d[mm]	l[mm]	lg[mm]	Qty per Strip	Recommended RPM[tr/min]	Quik Drive Attachment	Qty per Box	Weight[kg]
DTHQ51E	6.2	4.2	51	37	30.0	2500.0	QDPR051E / QDPR064E / QD76KE	2000.0	6.6
DTHQ64E	6.2	4.2	64	50	30.0	2500.0	QDPR064E / QD76KE / QDPR076SKE	1500.0	6.2
DTHQ76E	6.2	4.5	76	55	30.0	2500.0	QD76KE / QDPR076SKE	1000.0	6.2

Copyright by Simpson Strong-Tie®