Technical Sheet


TBG
Truck Bed Screw

The TBG heavy duty truck bed screw is perfect for fixing timber to steel frames. It has a countersunk ribbed flat head, self tapping thread and drill point with wings. The wings ream a hole larger in the timber and break off when they hit the steel. This allows the timber to be pulled tight to the steel. Suitable for fixing to steel up to 5mm thick. TBG screws are suitable for all types of timber including Keruing hardwood and WISA plywood. They are also mechanically galvanised and so are suitable for outdoor use.

SC 3

EPD EN 15804

YZP



OUTDOOR

Features

Material

- Steel - N2000® mechanically galvanised

Benefits

- Countersunk ribbed flat head for neat finish
- Suitable for outdoor use
- Self tapping thread
- Winged drill point to help clear hole and penetrate steel
- Driver bits included (BIT3SUE)







Applications

Support

- Used for fixing to steel or aluminium
- Maximum recommended steel thickness 5mm

Common Applications

- Truck beds and trailer floors
- Mezzanine floors
- Modular construction
- Mobile homes
- Caravans
- Boat building

Technical Sheet

TBG
Truck Bed Screw

Technical Data



Dimensions and caracteristics values


Reference	Fasteners Dimensions[mm]		
	QD information		Other
	Compatible devices	Max. rotational speed[tr/min]	Weight[kg]
TBG645E	QDHSD60E	1700 - 2000	0.008
TBG660E	QDHSD60E / QDHSD75E	1700 - 2000	0.011

TBG
Truck Bed Screw

Installation


Fasteners

s



TBG
Truck Bed Screw

Options



Countersunk head



Fine Thread



Drill Point with Wings

Copyright by Simpson Strong-Tie®