

Technical Sheet

WSC
WSC WOOD FLOORING Screw, Coarse Thread

WSC is a screw with a sharp point and coarse thread, suitable for wood to wood applications such as flooring.





Features

Material

- Yellow zinc dichromate

Benefits

- Wood to wood applications
- Coarse thread
- WSC32E has Type 17 point and nibs under the head
- WSC38E has a sharp point without nibs under the head
- Bit (BIT2SE) included

Applications

Header member

- Solid wood, composite wood, glued laminated timber,
- Wood frame.


Applications

- Subfloor installation

Technical Sheet

WSC
WSC WOOD FLOORING Screw, Coarse Thread

Technical Data



Dimensions and caracteristics values


Reference	Fasteners Dimensions
	Other
	Weight[kg]
WSC32E	0.003
WSC38E	0.003
WSC38E: ohne Unterkopfrippen und Schneidspitze!	

Mechanical properties (EN14592)

Reference	Screw Parameters				
	Characteristic parameters				
	Characteristic moment of elasticity - My,k[Nm]	Characteristic pullout parameter[N/mm²]	Characteristic head traversal parameter[N/mm²]	Characteristic pulling capacity[kN]	Characteristic resistance to torsion - $R_{tor,k}$[Nm]
WSC32E	3.6	11.5	8.1	7	5.1
WSC38E	3.6	11.5	8.1	7	5.1

WSC
WSC WOOD FLOORING Screw, Coarse Thread

Options



Countersunk Head with Nibs



Single Thread



Tapered tip

Copyright by Simpson Strong-Tie®